NNuTechCConveyorCComponents

Technical Data Sheet

1-495 McGeachie Drive Milton, ON, L9T 3L5 Toll Free: 1 (877) 639-2358 Phone: (905) 876-9339 Fax: (905) 876-9313

Product:

B120 PVC Rough Top

Description

This uni-ply construction PVC belt features high traction with its impression cover. This is an ideal belt for many incline/decline applications that require safe handling and positive movement. The all polyester interwoven carcass provides low-stretch for handling boxes, plastic, paper, corrugated cardboard and wood.

Physical Properties	
Туре:	Rough Top Belt
Color:	Black
# of Fabric Plies:	1 inter - woven, 1 solid woven
Fabric Top Material:	Polyvinylchloride (PVC)
Fabric Bottom Material:	Polyester (PET) fabric
Profile Top side:	Grip structure
Profile Bottom side:	Brushed
Total Thickness:	0.25"
Technical Data	
Temperature Range:	-18 to 82 C
Joining Methods:	#1 Clipper, #7 Alligator, #125 Staple
Antistatic:	No
Oil and Grease Resistant:	Yes
Pulley	
Min Pulley Diameter:	2" Clipper, 2" Alligator, 3" Staple
Carrying Rollers	Yes
Slider Bed	Yes
Trough Installation	No
Standards	
FDA food contact	No

Disclaimer:

The information contained in these Technical Data sheets is subject to change due to continuous developments where Data sheets are regenerated. Please check for the most up to date Data Sheets. If any other information is required please contact our sales team.