Technical Data Sheet

1-495 McGeachie Drive Milton, ON, L9T 3L5 Toll Free: 1 (877) 639-2358 Phone: (905) 876-9339

Fax: (905) 876-9313

Product: Eagle Orange 85 Non-Reinforced Flat

Description Eagle Orange 85 Non-Reinforced Flat Belting is constructed of solid polyurethane

with an 85 Shore A durometer that provides excellent abrasion resistance, high

elasticity, and is also self-tensioning.

Specifications

Profile shape: Flat

Profile size: .055"x.375", .062"x.500", .062"x.75"w/gde, .062"x1.50", .062"x1.75", .062"x2.00",

.062"x3.00", .078"x.750", .090"x1.00", .090"x1.25", .090"x1.50", .090"x2.00",

.125"x.625", .125"x1.00", .250"x.625"

Reinforcement: None Color: Orange

Compliancy: FDA, REACH, RoHS


Durometer: 85A

Material: Polyurethane Package Length: 100'/30.5m

Physical Properties

Eagle Orange 85 Non-Reinforced Flat

Hardness	85A
FDA Compliant Materials	Yes
Coefficient of Friction	Stainless Steel: .70; Steel: .60; UHMW: .45
Temperature Range	-22°F to +150°F; -30°C to +66°C



^{*} w (width) is the widest part of the belt. h (height) is the tallest part of the belt.

^{**} belt has .156" radius guide.